



A brand of **TOTAL**

ELF PERFORMANCE SUPER D 10W



Monograde lubricant for hydraulic applications

APPLICATIONS

- ELF PERFORMANCE SUPER D 10W is a **mineral** lubricant recommended for **hydraulic systems** and **transmissions**
- This lubricant is particularly adapted to **on-road** and **off-road** applications: construction, mining, agriculture.

APPROVALS

Specifications

API CF/SF

PERFORMANCES AND CUSTOMER BENEFITS

- ELF PERFORMANCE SUPER D 10W retains **excellent anti-wear protection**.
- Its **anti-rust** and **anti-corrosion properties** protect the hydraulic circuit components and ensure long equipment life.
- ELF PERFORMANCE SUPER D 10W exhibits **good resistance to oxidation**, avoiding oil thickening and preventing the formation of deposits and varnishes.

PHYSICAL AND CHEMICAL CHARACTERISTICS

ELF PERFORMANCE SUPER D 10W

		Method	Value
Density at 15°C	kg/m ³	ASTM D1298	881
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	34
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	5.8
Viscosity Index	-	ASTM D2270	112
Flash point	°C	ASTM D92	>220
Pour Point	°C	ASTM D97	-33
T.B.N	mgKOH/g	ASTM D2896	11
Sulphated Ash	% m/m	ASTM D874	1.54

The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

TOTAL LUBRIFIANTS

562 avenue du Parc de l'Île
92029 Nanterre
FRANCE

ELF PERFORMANCE SUPER D 10W

Update : 01/2015



*This lubricant does not cause adverse health effects when used in the intended application.
A safety datasheet, is accessible on request from your local dealer.*