



A brand of **TOTAL**

EVOLUTION 400 20W-50



Premium mineral oils designed for petrol and diesel engine oil.
Suitable for use under standard conditions.

APPLICATIONS

Old gasoline and diesel car engines

• These oils can be used with petrol or diesel engine technologies without particulate filters and engines built prior to 2001 and designed for use with mineral oils in these viscosities.

In all conditions

• Suitable for all conditions (in town, on highways or motorways); Meets needs of motor manufacturers regarding extended oil change intervals

Refer to the maintenance book of your vehicle to know the recommendation of the

PERFORMANCES

International specifications

API SL/CF

CUSTOMER BENEFITS

- Protection and reliability
- Protects engines against deposits.
- Oil film able to withstand high operating temperatures
- Standard drain interval.

CHARACTERISTICS

	Method	Units	SAE Grade 20W-50
Density at 15°C	ASTM D1298	Kg/m ³	882,9
Viscosity at 40°C	ASTM D445	mm ² /s	157,1
Viscosity at 100°C	ASTM 445	mm ² /s	17,8
Viscosity index	ASTM D2270	-	127
Pour point	ASTM D97	°C	-30
Flash point	ASTM D92	°C	> 230

The typical characteristics mentioned represent mean values

TOTAL LUBRIFIANTS – Immeuble Spazio
562, avenue du Parc de l'île
92029 Nanterre cedex
France

EVOLUTION 400 20W-50

Last update of this datasheet: 08/2017



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard.
A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.