



A brand of **TOTAL**

## PERFORMANCE GAS LA 15W-40



**Mineral lubricant suitable for gas engines (NGV or LPG).**

### APPLICATIONS

- ELF PERFORMANCE GAS LA 15W-40 is a mineral lubricant adapted to **NGV** (natural gas vehicles) and **LPG** (liquefied petroleum gas) engines in urban transport (especially buses, deliveries and waste collecting vehicles).
- With its low ash content, ELF PERFORMANCE GAS LA 15W-40 protects **Cummins'** gas engines.

### APPROVALS

Meets performance levels Cummins CES 20074  
ISUZU

### PERFORMANCES AND CUSTOMER BENEFITS

- ELF PERFORMANCE GAS LA 15W-40 has **excellent thermal stability** and oxidation and nitro-oxidation resistance. Its **low ash content** (0.5%) avoids spark plug fouling and deposits formation in the combustion chamber. ELF PERFORMANCE GAS LA 15W-40 is perfectly adapted to gas engines.
- ELF PERFORMANCE GAS LA 15W-40 contains **excellent viscosity stability in service**, guaranteeing effective engine protection in severe conditions.

### PHYSICAL AND CHEMICAL CHARACTERISTICS

ELF PERFORMANCE GAS LA 15W-40		Method	Value
Density at 15°C	kg/m <sup>3</sup>	ASTM D1298	884
Kinematic Viscosity at 40°C	mm <sup>2</sup> /s	ASTM D445	104.5
Kinematic Viscosity at 100°C	mm <sup>2</sup> /s	ASTM D445	14
Viscosity Index	-	ASTM D2270	136
Flash point	°C	ASTM D92	>200
Pour Point	°C	ASTM D97	<-24
T.B.N	mgKOH/g	ASTM D2896	5
Sulphated Ash	% m/m	ASTM D874	0.5

*The features mentioned above are average values obtained with some variability in production and do not constitute a specification.*