

Pantere Drive 5W30



High Performance Low Friction Motor Oil

Pantere Drive 5W30 is a modern fuel-efficient high performance low friction motor oil with the latest Pantere Tungsten-technology. It decreases the friction in the motor because of the exceptional new Tungsten-technology. Thereby it reduces the fuel consumption and reaches a longer motor lifetime.

- Performance optimization by minimized frictional resistance
- Less wear by optimized friction
- Optimal wear protection
- Excellent cold starting performance
- Best motor cleanliness
- Cost-effective all-season oil with noticeable fuel reduction
- Outstanding low friction properties
- Takes care for the environment by reduced emissions of CO₂ and particles

Pantere Drive 5W30 is based on an engine-oil which matches the following specification: ACEA A5/B5/C2, API SM, ILSAC GF-4, Ford WSS-M2C 913-C

It is adapted for passenger car engines, diesel without or without particulate filter or gasoline

FOR JAGUAR/ FORD/ CITROËN/ PEUGEOT/ TOYOTA/ MITSUBISHI/ DAIHATSU/ SUBARU

Pantere Drive 5W30	value	unit	method
Density (15 °C)	874	kg/m ³	DIN 51 757
Viscosity (40 °C)	101	mm ² /s	DIN 51 562
Viscosity (100 °C)	14,5	mm ² /s	DIN 51 562
Viscosity Index	148		DIN ISO 2909
CCS (-25°C)	6900	mPa.s	DIN 51 377
Pourpoint	- 36	°C	DIN ISO 3016
Flashpoint	220	°C	DIN ISO 2592

Pantere GmbH
Münsterstrasse 6a
49565 Bramsche
Tel. 05461 / 95 88 22-0
Fax 05461 / 95 88 22-9