

Pantere Dynamic 5W30



High Performance Low Friction Motor Oil

Pantere Drive 5W30 is a modern fuel-efficient high performance low friction motor oil with the latest Pantere Tungsten-technology. It decreases the friction in the motor because of the exceptional new Tungsten-technology. Thereby it reduces the fuel consumption and reaches a longer motor lifetime.

- Performance optimization by minimized frictional resistance
- Less wear by optimized friction
- Outstanding wear protection
- Outstanding low friction properties
- Demonstrable fuel economy and environmentally friendly
- Mid SAPs – Oil with low ash content for diesel engines with Diesel Particular Filter

Pantere Dynamic 5W30 is based on an engine-oil which matches the following specification: ACEA A3/B4/C3, API SM/CF, GM DEXOS 2 and approval from VW 502 00/505 00/ 505 01 (PD), MB 229.51, BMW Longlife-04.

It is adapted for passenger car engines, diesel without or without particulate filter or gasoline

MERCEDES BENZ/ BMW/ AUDI/ VW/ OPEL

Pantere Dynamic 5W30	value	unit	method
Density (15 °C)	856	kg/m ³	DIN 51 757
Viscosity (40 °C)	71,5	mm ² /s	DIN 51 562
Viscosity (100 °C)	12,1	mm ² /s	DIN 51 562
Viscosity Index	166		DIN ISO 2909
CCS (-25°C)	5910	mPa.s	DIN 51 377
Pourpoint	- 39	°C	DIN ISO 3016
Flashpoint	232	°C	DIN ISO 2592

Pantere GmbH
Münsterstrasse 6a
49565 Bramsche
Tel. 05461 / 95 88 22-0
Fax 05461 / 95 88 22-9