

Pantere Power 5W40



High Performance Low Friction Motor Oil

Pantere Power 5W40 is a modern fuel-efficient high performance low friction motor oil with the latest Pantere Tungsten-technology. It decreases the friction in the motor because of the exceptional new Tungsten-technology. Thereby it reduces the fuel consumption and reaches a longer motor lifetime.

- Performance optimization by minimized frictional resistance
- Less wear by optimized friction
- Outstanding wear protection
- Outstanding low friction properties
- Demonstrable fuel economy and environmentally friendly
- Mid SAPs – Oil with low ash content for diesel engines with Diesel Particular Filter

Pantere Power 5W40 is based on an engine-oil which matches the following specification: ACEA A3/B4/C3, API SM/CF and approval from VW 502 00/ 505 00/ 505 01(PD), MB 229.51, BMW Longlife-04

It is adapted for passenger car engines, diesel without or without particulate filter or gasoline

MERCEDES BENZ/ BMW/ AUDI/ VW

Pantere Power 5W40	value	unit	method
Density (15 °C)	853	kg/m ³	DIN 51 757
Viscosity (40 °C)	75,2	mm ² /s	DIN 51 562
Viscosity (100 °C)	13,0	mm ² /s	DIN 51 562
Viscosity Index	175		DIN ISO 2909
CCS (-25°C)	6060	mPa.s	DIN 51 377
Pourpoint	- 36	°C	DIN ISO 3016
Flashpoint	232	°C	DIN ISO 2592

Pantere GmbH
Münsterstrasse 6a
49565 Bramsche
Tel. 05461 / 95 88 22-0
Fax 05461 / 95 88 22-9