

Pantere Racing X 10W60



Fully Synthetic High Performance Low Friction Motor Oil

Pantere Racing X 10W60 is a modern fuel-efficient fully synthetic high performance low friction motor oil with the latest Pantere Tungsten-technology. It decreases the friction in the motor because of the exceptional new Tungsten-technology. Thereby it reduces the fuel consumption and reaches a longer motor lifetime.

- Performance optimization by minimized frictional resistance
- Less wear by optimized friction
- Extreme wear protection under any operating conditions
- Outstanding cold-starting performance
- Optimal lubrication even at high thermal conditions
- Highest piston cleanliness

Pantere Racing X 10W60 is based on an engine-oil which matches the following specification: ACEA A3/B3, API SL/CF

It is adapted for modern performance enhanced passenger car engines, diesel or gasoline, especially for fuel-injected and turbo charged cars.

FOR RACING CARS

Pantere Racing X 10W60	value	unit	method
Density (15 °C)	859	kg/m ³	DIN 51 757
Viscosity (40 °C)	178,8	mm ² /s	DIN 51 562
Viscosity (100 °C)	25,5	mm ² /s	DIN 51 562
Viscosity Index	177		DIN ISO 2909
CCS (-25°C)	4690	mPa.s	DIN 51 377
Pourpoint	- 42	°C	DIN ISO 3016
Flashpoint	224	°C	DIN ISO 2592

Pantere GmbH
Münsterstrasse 6a
49565 Bramsche
Tel. 05461 / 95 88 22-0
Fax 05461 / 95 88 22-9