

Pantere Speed 5W30



High Performance Low Friction Motor Oil

Pantere Speed 5W30 is a modern fuel-efficient high performance low friction motor oil with the latest Pantere Tungsten-technology. It decreases the friction in the motor because of the exceptional new Tungsten-technology. Thereby it reduces the fuel consumption and reaches a longer motor lifetime.

- Performance optimization by minimized frictional resistance
- Less wear by optimized friction
- Outstanding wear protection
- Outstanding low friction properties
- Demonstrable fuel economy and environmentally friendly
- Mid SAPs – Oil with low ash content for diesel engines with Diesel Particular Filter

Pantere Speed 5W30 is based on an engine-oil which matches the following specification: ACEA A3/B4/C3 and approval from MB 229.51, BMW Longlife-04, VW 504 00/ 507 00

It is adapted for passenger car engines, diesel without or without particulate filter or gasoline.

MERCEDES BENZ/ BMW/ AUDI/ VW/ SEAT/ SKODA/ SAAB/ VOLVO

Pantere Speed 5W30	value	unit	method
Density (15 °C)	850	kg/m ³	DIN 51 757
Viscosity (40 °C)	70,4	mm ² /s	DIN 51 562
Viscosity (100 °C)	11,7	mm ² /s	DIN 51 562
Viscosity Index	162		DIN ISO 2909
CCS (-25°C)	6200	mPa.s	DIN 51 377
Pourpoint	- 49	°C	DIN ISO 3016
Flashpoint	246	°C	DIN ISO 2592

Pantere GmbH
Münsterstrasse 6a
49565 Bramsche
Tel. 05461 / 95 88 22-0
Fax 05461 / 95 88 22-9