

Pantere Vmax 0W40



Fully Synthetic Low Friction Motor Oil

Pantere Vmax 0W40 is a modern fuel-efficient fully synthetic low friction motor oil with the latest Pantere Tungsten-technology. It decreases the friction in the motor because of the exceptional new Tungsten-technology. Thereby it reduces the fuel consumption and reaches a longer motor lifetime.

- Performance optimization by minimized frictional resistance
- Less wear by optimized friction
- Excellent cold starting performance
- High wear and corrosion protection.
- Optimal motor protection against deposit formation
- Demonstrable fuel economy and environmentally friendly
- All season using because of its extreme viscosity range

Pantere Vmax 0W40 is based on an engine-oil which matches the following specification: ACEA A3/B3, API SJ/CF

It is adapted for passenger car engines, diesel without particulate filter or gasoline, especially for sporty driving.

FOR MOTORSPORT

Pantere Vmax 0W40	value	unit	method
Density (15 °C)	864	kg/m ³	DIN 51 757
Viscosity (40 °C)	74,8	mm ² /s	DIN 51 562
Viscosity (100 °C)	13,2	mm ² /s	DIN 51 562
Viscosity Index	180		DIN ISO 2909
CCS (-25°C)	6200	mPa.s	DIN 51 377
Pourpoint	- 54	°C	DIN ISO 3016
Flashpoint	235	°C	DIN ISO 2592

Pantere GmbH
Münsterstrasse 6a
49565 Bramsche
Tel. 05461 / 95 88 22-0
Fax 05461 / 95 88 22-9