

# SRS Viva 1 synth racing, SAE 5W-50

## Synthetic High Performance Engine Oil

September 2007

### Properties

SRS VIVA 1 synth Racing is a synthetic high-performance motor oil of viscosity grade SAE 5W-50.

Synthetic components and innovative additives matched to them ensure that the demands of today's practice are met.

The improved quality of SRS VIVA 1 synth Racing is specially a result of further improved anti-wear and engine cleanliness, even with extended oil drain intervals.

The low cold-viscosity combined with an extreme high-temperature viscosity provide unsurpassed protection for the engines.

### Application

SRS VIVA 1 synth Racing is suitable as a high-performance engine oil for use in discerning new generation engines.

It is recommended for passenger car gasoline and diesel engines, including the multivalved and for turbocharger and direct injected engines under all operating conditions.

### Performance / Specifications

SAE Grade	5W-50
API	SM/CF
ACEA	A3/B4

Typical data		Test method	SRS VIVA 1 synth racing
SAE Grade		DIN 51 511	5W-50
Density at 15°C	g/cm <sup>3</sup>	DIN 51 757	0,857
Viscosity at – 30°C	mPa s	DIN 51 377	6.300
Viscosity at 40°C	mm <sup>2</sup> /s	DIN 51 562	102
Viscosity at 100°C	mm <sup>2</sup> /s	DIN 51 562	16,5
Viscosity Index (VI)		DIN ISO 2909	176
Flash point COC	°C	DIN ISO 2592	225
Pour point	°C	DIN ISO 3016	- 27
Total Base Number	mg/KOH/g	DIN ISO 3771	10,1
Sulphate Ash	g/100 g	DIN 51 575	1,2

SRS VIVA 1 synth racing, SAE 5W-50 is a product of the H&R ChemPharm GmbH

The above values may vary within the commercial limits (mm<sup>2</sup>/s = cSt)