

## Material safety data sheet

Trade name: **Swd Adhesol SW****1. Identification of the substance / preparation and of the company / undertaking**

Identification of the product  
 Trade name Swd Adhesol VDL  
 Type of product Slideway-Lubeoil, ISO VG 46,68,100,150,220, 320 und 460

Company name SWD Lubricants GmbH & Co KG  
 Am Schlütershof 26  
 47059 Duisburg

Product-management Mr. P. Fritsch  
 Tel: 0203 / 31919 400 Fax: 0203 / 34665 40

**2. Composition / Information of ingredients**

Chemical characterisation Preparation of refined mineral oil and Additives

Substances presenting a health hazard

Components	Symbole	Risk-phrases	Wt %	EINECS-No
Baseoil (Crudeoil) C20 – C50		DMSO-Extract < 3%	> 95	276-738-4
Alkylthiodiazole	Xi	43	> 1,0	-

**3. Hazard identification**

Dangerous substances No substances above the limit values

Main hazards On prolonged skin contact it may cause irritations and/or sensitiveness.  
  
The components and the product may be considered not to be essentially dangerous under normal conditions of use.

Environmental hazards When appropriately and responsibly handled, the product should not be dangerous for the environment.  
In case of spillage or inappropriate use, it may however impair water and soil properties.

**4. First-aid measures**

Route of exposure  
 – Inhalation In case of inhalation of small quantities, no important effect is observed.  
Inhalation of aerosols may cause mild irritation of the throat.  
Remove affected person to fresh air.  
Get medical advice if sensation of shortness of breath occurs after inhalation of high concentration of aerosols.

– Skin contact Change contaminated clothing immediately.  
Wash skin as soon as possible with soap and water.

## Material safety data sheet

**Trade name:** **Swd Adhesol SW**

In case of skin injury from high-pressure equipment, there is a risk of product injection under the skin. Injured must therefore be sent to a hospital, even there are few or no symptoms.

– Eye contact

Flush immediately with plenty of water, holding eyelids open, for at least 15 minutes.

– Ingestion

Do not induce vomiting. Risk of pulmonary irritation of the lung. Possible risk of vomiting and diarrhoea.

Seek medical advice immediately

## 5. Fire-fighting measures

Fireclass

B

Technical measures

Evacuate non-essential personnel.  
Keep tankage cool by continuous spraying with water.

Suitable extinguishing media

Carbon dioxide, dry chemicals, foam.

Unsuitable extinguishing media

Do not use water jets in early stages of extinguishing fire since they could help to spread the flames.

Combustion products

Combustion forms: carbon mono- and dioxide and cracking products. Their inhalation is likely to be harmful.

Protectiv equipment for firefighters

The fire brigade shall wear suitable breathing equipment.

Protectiv measures

Do not heat above the flashpoint and do not build oil mist.

## 6. Accidental release measures

Personal precautions

Remove sources of ignition. No smoking.  
Ventilate the working place thoroughly.  
Avoid contact with skin and eyes and inhalation.  
Wear suitable breathing equipment in case of exposure to vapour and fumes

Environmental precautions

If possible stop spill at the source.  
Take up small spills with chemical absorbent.  
Avoid discharge of the material in a sewer or cause a ground contamination. Report large spills direct to the authorities.

## 7. Handling and storage

Handling

Avoid producing or diffusing oil mist in the air.  
Store away from heating sources. Avoid electrical build up with connecting to earth.  
Avoid contact with flames and sparks.

Storage

Ventilate work places thoroughly.  
Store out of sunshine or other sources of radiation.  
Use only containers, joints, pipes etc.. made in a material suitable for use with hydrocarbons.

## Material safety data sheet

**Trade name:** **Swd Adhesol SW**

Obey the water protective regulation for handling and storage of water endangering products ( in Germany VwVwS)

### 8. Exposure controls and personal protection

Exposure controls	For „ mineral oil mist“ a level of 5 mg/m <sup>3</sup> in atmosphere is recommended (ACGIH – TLV – 8 h TWA) or 10 mg/m <sup>3</sup> ( ACGIH – TLV 15 min STEL )
Recommended monitoring	DGMK, Nr. 21A (1987)
TA Luft Kl. III	50 mg/m <sup>3</sup> at mass-stream of 0,5 kg/h or more.
Personal protection	When exposure is likely, protective clothing must be worn
Skin protection	Oil resistant gloves (recommended material: Nitrile, Neoprene) During use in engines, contamination with low levels of combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermitted skin contact with used motor oils is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water.
Breathing protection	Wear suitable breathing equipment in areas with poor ventilation and noticeable fumes and fogs.
Eye protection	Goggles /spectacles
Industrial hygiene	Do not store near food products Do not wipe hands with clothes or rags which have been used for Cleaning. Remove all contaminated clothing immediately. Use disposable “ wipes” rather than rags or cotton waste. Never put oil-contaminated material or tools into pocket.

### 9. Physical and chemical properties

Physical state at 20°C	liquid
Colour	yellow to amber
Odour	oily
Pour point	< - 9 °C
Initial boiling point	not determined
Final boiling point	not determined
Flashpoint	> 200 °C
Thermal decomposition	> 350 °C
Ignition temperature	230 °C
Behaviour with water at 20°C	non miscible
Explosion values	(oil mist or thermal treatment) upper 6,5 Vol% lower 0,6 Vol%
Vapour pressure	not determined
Density	882 - 925 kg/m <sup>3</sup> at 15 °C

### 10. Stability and reactivity

## Material safety data sheet

**Trade name:** **Swd Adhesol SW**

Stability Decomposition products	Stable under normal operating conditions With oxygen forms: Carbon dioxide, water. With poor oxygen forms: Carbon monoxide, cracking products.
-------------------------------------	--

## 11. Toxicological information

Rat oral LD 50	> 2000 mg/kg
Ingestion	In case of small quantities, no important effect is observed. In case of ingestion of larger amounts: abdominal pain, diarrhoea, ...
Inhalation	Vapour or aerosols may cause irritation of upper respiratory tract.
Skin contact	Prolonged or frequent contacts may cause skin irritation.
Eye contact	Mildly irritating
- Carcenogenicity	The Product is not considered to be a carcinogen. The oil-components contains less than 3 % DMSO extract measured by IP 346. It needs not to be classified as T, R45. (nota L)
- Sensitiation	The product contains no sensitizing agents in the range from 0.1 to 1.0 Wt %
- Mutagenic	The product is not considered to be a mutagen.
- Reproductiv toxicity	The product is not considered to be a teratogen.

## 12. Angaben zur Ökologie

Mobility	
- Air	There is a slow loss by evaporation.
- Soil	Because of its physico-chemical properties the product has generally low soil mobility.
- Water	The product is in general not water soluble. The product spreads out on the surface of the water. A small fraction of the constituents will be dissolved.
Persistence and degradability	The product is easily knocked down from a water phase by a mechanical separator.
Biodegradation	not readily bio gradable
Bio accumulative potential	no information available
Log P n octano/water at 20 °C	> 6 not relevant for aquatic toxicity (Concawe product dossier)
Ecotoxicity	no information available

## Material safety data sheet

**Trade name:** **Swd Adhesol SW**

### 13. Disposal considerations

Disposal The product is considered as industrial waste. Dispose in a safe manner in accordance with the local/ national regulations.

EC-Waste No. 13 02 05 (EC-Waste-Catalog)

### 14. Transport Information

ADR/RID Not restricted for transport  
 ADNR Not restricted for transport  
 IMO-IMDG Not restricted for transport  
 ICAO/ IATA Not restricted for transport

Not classified as dangerous good in according to transportation rules.

### 15. Regulatory Information

Labelling and Classification Not classified according to EEC directives 67/584/EEC (dangerous substances) and 88/379/EEC (dangerous preparations)

Symbols none

R-phrases none

S-phrases none

This product contains less than 3 % DMSO extract as measured by IP 346; it needs not to be classified as T, R45: " May cause cancer". (Nota L)

Germany  
 Wassergefährdungsklasse WGK 2 – water endangering  
 Classification in accordance to the German regulation of water endangering substances (VwVwS).

### 16. Other Information

Relevant R-phrases R43 May cause sensitization by skin contact.

Further information During use in engines, contamination of oil with low levels of combustion products occurs. Used motor oils have shown to cause skin cancer in mice following repeated application and continuous exposure.  
 Brief or intermitted skin contact with used motor oils is not expected to have serious effects in humans, if the oil is thoroughly removed by washing with soap and water.

### Important:

## Material safety data sheet

---

**Trade name:** **Swd Adhesol SW**

---

The information in this Data Sheet applies only to the product designated herein and is based on our experience and on the data available to us at the time of its issue and is accurate to the best of our knowledge.

The customer is strongly advised to observe and ensure that all employees and customers observe all directions contained herein.

However, no warranty is made or implied that the information is accurate or complete and no liability will be accepted whatsoever arising out of the use of the information or the products designated herein.

---