

swd TWOKE SYNMIX ULTRA

Synthetic High Performance 2-Stroke Oil

Description

swd TWOKE SYNMIX ULTRA is a fully synthetic 2-stroke motor oil to be used in air- and water-cooled road and racing engines. Its capacity exceeds the actually most stringent specification requirements of all 2-stroke motor manufacturers.

Properties

swd TWOKE SYNMIX ULTRA is produced from high-temperature proof and most lubricious synthetic base oils and special low-ash additives of latest technology, which assure

- optimal motor lubrication even under high-speed racing conditions
- reduction of deposits in the combustion chamber, at the sparking plugs, in the circular grooves and the exhaust system
- improved pollution control by scentless and smokeless combustion
- universal use in all lubrication systems (fresh oil lubrication, auto-lube systems, mixed lubrication) and for all gasoline fuels

Application

swd TWOKE SYNMIX ULTRA was designed for the use in high-speed racing engines of motor cycles and carts as well as for normal sports engines or for 2-stroke engines, which require disproportionately high lubrication guarantee.

Qualification

- ❖ API TC
- ❖ JASO FC
- ❖ ISO - L - EGD

Typical Values

swd TWOKE SYNMIX ULTRA	unit	value	method
Density at 15°C	kg/m ³	883	DIN 51 757
Color		green	visual
Viscosity at 40°C	mm ² /s	63,3	DIN 51 562
Viscosity at 100°C	mm ² /s	10,7	DIN 51 562
Viscosity index		160	DIN ISO 2909
Pourpoint	°C	-39	DIN ISO 3016
Flash point	°C	98	DIN ISO 2592
Sulphated ash	% mass.	0,18	DIN 51 575

Article-No. : 32160

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further informations to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Phone: 0203 / 3191940
Fax: 0203 / 3466540

