

swd FAVORIT E7

10W-40

High Performance Fuel Efficiency Oil for Diesel Engines in Trucks and Passenger Cars

Product Description

swd FAVORIT E7 SAE10W-40 is a high performance motor oil for modern heavily stressed diesel engines inclusive turbo charger. It meets the requirements of the highest engine-power class for Diesel engines, and thus it falls in the category UHPD oil (high performance Diesel oil). By its viscosity range, preferred by the constructors, it belongs to the fuel economy oils and thereby it contributes to reduced fuel consumption. Severe requirements of gasoline engines. This makes it being excellent provider for mixed-fleet.

swd FAVORIT E7 SAE 10W-40 gives following advantages:

- excellent thermal/oxidative stability reduces sludge built-up und deposits.
- allows maximum oil drain intervals
- highest protection against wear and corrosion
- reduces oil aging, even at high temperatures.
- best seal and elastomer compatibility
- an all-seasons oil

swd FAVORIT LMF 10W-40 is especially recommended for fleets operating in severe on and off-highway service applications, as well as for passenger cars and vans with Diesel engines.

Specifications

ACEA E7 / B4 / A3	Scania LDF
API CI-4 / SL	VOLVO VDS-2*
MB-Blatt 228.5* / 229.1*	Renault RVI-RXD
MAN M 3277* CRT	Allison C-4
MTU Typ3	VW 505.00

* approved under different name

Typical Properties

swd FAVORIT E7 10W-40	unit	value	method
Density at 15°C	kg/m ³	876	DIN 51 757
Viscosity at 40°C	mm ² /s	104,5	DIN 51 562
Viscosity at 100°C	mm ² /s	14,5	DIN 51 562
Viscosity Index		138	DIN ISO 2909
CCS at -25°C	mPa.s	6910	DIN 51 377
Pourpoint	°C	-45	DIN ISO 3016
Flashpoint	°C	220	DIN ISO 2592

Article-Number : **31057**

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further informations to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Tel.: 0203 / 3191940
Fax: 0203 / 3466540