



swd PRIMUS ULTRA

0W-30

FULLY SYNTHETIC MULTIGRADE FUEL ECONOMY OIL

Properties

swd PRIMUS LIGHT SAE 0W-30 is a fully synthetic high performance fuel economy oil for gasoline and diesel engines in passenger cars. While fulfilling the requirements of the Volkswagen AG according VW 503 01, 502 00 and 505 00 it meets one of the stringentest specifications of motor car manufacturers world wide. It is used in engines with direct injection, turbo charger and multivalve technics, if a special oil of this specification is recommended.

swd PRIMUS LIGHT SAE 0W-30, by its progressive formulation and due to the mechanism of the hightech additives, protects the motor against wear and sludge built-up. The special viscosity range provides to the engine extreme fuel economy as well as outstanding cold starting properties. Furthermore high lubricating film reliability is assumed, even at thermal load. By its total properties the oil has got a great potential for saving fuel, and it contributes to ensure the constant performance of the motor a long time through.

❖ Qualification

- ❖ ACEA A3 / B4
- ❖ API SJ / CF
- ❖ VW 502.00 / 505.00 / 503.01

◆ Approvals

- ◆ MB-page 229.3
- ◆ BMW Longlife-98

Typical Properties

swd PRIMUS ULTRA SAE 0W-30	unit	value	method
Density at 15°C	kg/m ³	855	DIN 51 757
Viscosity at 400°C	mm ² /s	65	DIN 51 562
Viskosität bei 100°C	mm ² /s	11,7	DIN 51 562
Viscosity Index		177	DIN ISO 2909
Pourpoint	°C	-54	DIN ISO 3016
Flash point	°C	220	DIN ISO 2592

Article-No. : 30170

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further informations to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Phone: 0203 / 3191940
Fax: 0203 / 3466540