Material Safety Data Sheet

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

Material Name : Shell Clavus Oil 100 Uses : Refrigerator oil.

Product Code : 001A0149

Manufacturer/Supplier : Shell Deutschland Oil GmbH

Suhrenkamp 71-77 D-22335 Hamburg

Telephone : (+49) 40 6324-6255 **Fax** : (+49) 40 6321-051

Email Contact for : If you have any enquiries about the content of this MSDS

MSDS please email lubricantSDS@shell.com

Emergency Telephone

Number

: +49 (0)40 6324-5110

2. HAZARDS IDENTIFICATION

EC Classification : Not classified as dangerous under EC criteria.

Health Hazards : Not expected to be a health hazard when used under normal

conditions. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. High-pressure injection under the skin may cause serious damage including local necrosis. Used

oil may contain harmful impurities.

Signs and Symptoms : Local necrosis is evidenced by delayed onset of pain and

tissue damage a few hours following injection. Oil

acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.

Safety Hazards : Not classified as flammable but will burn.

Environmental Hazards : Not classified as dangerous for the environment.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Preparation description: Highly refined mineral oil.

Additional Information : The highly refined mineral oil contains <3% (w/w) DMSO-

extract, according to IP346.

4. FIRST AID MEASURES

General Information : Not expected to be a health hazard when used under normal

conditions.

Inhalation : No treatment necessary under normal conditions of use. If

symptoms persist, obtain medical advice.

Skin Contact : Remove contaminated clothing. Flush exposed area with water

Effective Date 15.06.2008

Regulation 1907/2006/EG

Material Safety Data Sheet

and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention. When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop. Obtain medical attention even in the absence of apparent wounds.

Eye Contact : Flush eye with copious quantities of water. If persistent

irritation occurs, obtain medical attention.

Ingestion : In general no treatment is necessary unless large quantities

are swallowed, however, get medical advice.

Advice to Physician : Treat symptomatically. High pressure injection injuries require

prompt surgical intervention and possibly steroid therapy, to minimise tissue damage and loss of function. Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetics, and

wide exploration is essential.

5. FIRE FIGHTING MEASURES

Clear fire area of all non-emergency personnel.

Specific Hazards : Hazardous combustion products may include: A complex

mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic

compounds.

Suitable Extinguishing

Media

Unsuitable Extinguishing

Media

Protective Equipment for

Firefighters

: Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Do not use water in a jet.

Proper protective equipment including breathing apparatus must be worn when approaching a fire in a confined space.

6. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal. Observe all relevant local and international regulations.

Protective measures : Avoid contact with skin and eyes. Use appropriate containment

to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or

other appropriate barriers.

Clean Up Methods : Slippery when spilt. Avoid accidents, clean up immediately.

Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.

Version 1.0

Effective Date 15.06.2008 Regulation 1907/2006/EG

Material Safety Data Sheet

Additional Advice Local authorities should be advised if significant spillages

cannot be contained.

7. HANDLING AND STORAGE

General Precautions Use local exhaust ventilation if there is risk of inhalation of

> vapours, mists or aerosols. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine

appropriate controls for safe handling, storage and disposal of

this material.

Handling Avoid prolonged or repeated contact with skin. Avoid inhaling

> vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment

should be used.

Storage Keep container tightly closed and in a cool, well-ventilated

place. Use properly labelled and closeable containers. Storage

Temperature: 0 - 50°C / 32 - 122°F

Recommended Materials

For containers, or container linings use mild steel. **Unsuitable Materials**

For containers or container linings avoid PVC, polyethylene or

high density polyethylene.

Additional Information : Storage class: 10

Fire hazard classification: B.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

Exposure Controls The level of protection and types of controls necessary will vary

depending upon potential exposure conditions. Select controls

based on a risk assessment of local circumstances.

Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or

mist formed, there is greater potential for airborne

concentrations to be generated.

Personal Protective

Equipment

Respiratory Protection

Personal protective equipment (PPE) should meet

recommended national standards. Check with PPE suppliers. No respiratory protection is ordinarily required under normal

conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [boiling point

>65 °C (149 °F)] meeting EN141.

Hand Protection Where hand contact with the product may occur the use of

gloves approved to relevant standards (e.g. Europe: EN374,

MSDS_DE Print Date 14.07.2008

Effective Date 15.06.2008 Regulation 1907/2006/EG

Material Safety Data Sheet

US: F739) made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye Protection : Wear safety glasses or full face shield if splashes are likely to

occur. Approved to EU Standard EN166.

Protective Clothing : Skin protection not ordinarily required beyond standard issue

work clothes.

Monitoring Methods : Monitoring of the concentration of substances in the breathing

zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also

be appropriate.

Environmental Exposure

Controls

Minimise release to the environment. An environmental

assessment must be made to ensure compliance with local

environmental legislation.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Amber. Liquid.
Odour : Slight hydrocarbon.
pH : Not applicable.

Initial Boiling Point and

: > 280 °C / 536 °F estimated value(s)

Boiling Range

Pour point : Typical -27 °C / -17 °F

Flash point : Typical 210 °C / 410 °F (COC)

Upper / lower Flammability

or Explosion limits

: Typical 1 - 10 %(V) : > 320 °C / 608 °F

Auto-ignition temperature : > 320 °C / 608 °F

Vapour pressure : < 0,5 Pa at 20 °C / 68 °F (estimated value(s))

Density : Typical 906 kg/m3 at 15 °C / 59 °F

Water solubility : Negligible.

n-octanol/water partition : > 6 (based on information on similar products)

coefficient (log Pow)

Kinematic viscosity : Typical 100 mm2/s at 40 °C / 104 °F

Vapour density (air=1) : > 1 (estimated value(s)) Evaporation rate (nBuAc=1) : Data not available

10. STABILITY AND REACTIVITY

Stability : Stable.

Conditions to Avoid : Extremes of temperature and direct sunlight.

Materials to Avoid : Strong oxidising agents.

Hazardous : Hazardous decomposition products are not expected to form

Decomposition Products during normal storage.

Material Safety Data Sheet

11. TOXICOLOGICAL INFORMATION

Basis for Assessment : Information given is based on data on the components and the

toxicology of similar products.

Acute Oral Toxicity : Expected to be of low toxicity: LD50 > 5000 mg/kg , Rat
Acute Dermal Toxicity : Expected to be of low toxicity: LD50 > 5000 mg/kg , Rabbit
Acute Inhalation Toxicity : Not considered to be an inhalation hazard under normal

conditions of use.

Skin Irritation : Expected to be slightly irritating. Prolonged or repeated skin

contact without proper cleaning can clog the pores of the skin

resulting in disorders such as oil acne/folliculitis.

Eye Irritation : Expected to be slightly irritating.

Respiratory Irritation: Inhalation of vapours or mists may cause irritation.

Sensitisation : Not expected to be a skin sensitiser.

Repeated Dose Toxicity : Not expected to be a hazard.

Mutagenicity : Not considered a mutagenic hazard.

Carcinogenicity : Product contains mineral oils of types shown to be non-carcinogenic in animal skin-painting studies. Highly refined mineral oils are not classified as carcinogenic by the

mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC). Other components are not known to be associated with carcinogenic

effects.

Reproductive and Developmental Toxicity Additional Information : Not expected to be a hazard.

: Used oils may contain harmful impurities that have

accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with caution and skin contact avoided as far as possible. High pressure injection of product into the skin may lead to local

necrosis if the product is not surgically removed.

12. ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.

Acute Toxicity : Poorly soluble mixture. May cause physical fouling of aquatic

organisms. Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l (to aquatic organisms) (LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract). Mineral oil is not expected to cause any chronic effects to aquatic organisms at concentrations less than 1 mg/l.

Mobility : Liquid under most environmental conditions. Floats on water. If

it enters soil, it will adsorb to soil particles and will not be

mobile.

Persistence/degradability : Expected to be not readily biodegradable. Major constituents

are expected to be inherently biodegradable, but the product contains components that may persist in the environment.

Bioaccumulation : Contains components with the potential to bioaccumulate.

Other Adverse Effects : Product is a mixture of non-volatile components, which are not

Version 1.0

Effective Date 15.06.2008

Regulation 1907/2006/EG

Material Safety Data Sheet

expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.

13. DISPOSAL CONSIDERATIONS

Material Disposal : Recover or recycle if possible. It is the responsibility of the

waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in

drains or in water courses.

Container Disposal : Dispose in accordance with prevailing regulations, preferably to

a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

Local Legislation : Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

EU Waste Disposal Code (EWC): 13 08 99 oil waste not otherwise specified. Classification of waste is always the

responsibility of the end user.

14. TRANSPORT INFORMATION

ADR

This material is not classified as dangerous under ADR regulations.

RID

This material is not classified as dangerous under RID regulations.

ADNR

This material is not classified as dangerous under ADNR regulations.

IMDG

This material is not classified as dangerous under IMDG regulations.

IATA (Country variations may apply)

This material is not classified as dangerous under IATA regulations.

15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

EC Classification : Not classified as dangerous under EC criteria.

EC Symbols : No Hazard Symbol required

EC Risk Phrases : Not classified.
EC Safety Phrases : Not classified.
EINECS : All components

listed or polymer

exempt.

Version 1.0

Effective Date 15.06.2008 Regulation 1907/2006/EG

Material Safety Data Sheet

TSCA : All components

listed.

National Legislation

Water Pollution Class : WGK 1 - low hazard to waters (appendix 2, VwVwS,

preparations).

Other Information : Technische Anleitung Luft: Product not listed by name.

Observe section 5.2.5 in connection with section 5.4.9

16. OTHER INFORMATION

R-phrase(s)

Not classified.

MSDS Version Number : 1.0

MSDS Effective Date : 15.06.2008

MSDS Revisions : A vertical bar (|) in the left margin indicates an amendment

from the previous version.

MSDS Regulation : Regulation 1907/2006/EG

MSDS Distribution : The information in this document should be made available to

all who may handle the product.

Disclaimer : This information is based on our current knowledge and is

intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property

of the product.