



TOTAL DELTA ECO 5W-30



HIGH-PERFORMANCE-OIL FOR GASOLINE AND DIESEL ENGINES

USES

- Ensures easy cold start and fuel economies due to its extreme fluidity at low temperature.
- For all gasoline and diesel engines in passenger cars operating in the most severe conditions whatever the seasons.

PERFORMANCES

- API SJ / CF
- ACEA A1 / B1
- ILSAC GF-2
- FORD WSS M2C913-B

CHARACTERISTICS

- Provides a significant reduction of fuel consumption.
- Protects mechanical parts and fully preserves the engine power.
- Keeps the engine's most sensitive parts clean.
- Very good antioxidant, antirust, antifoaming properties.
- Excellent antiwear and anticorrosion properties.

| TYPISCHE KENNWERTE | METHODEN | EINHEITEN | DELTA ECO |
|-----------------------|-----------|--------------------|-----------|
| SAE-Klasse | DIN 51511 | - | 5W-30 |
| Dichte bei 15 °C | DIN 51757 | kg/m ³ | 852 |
| Viskosität bei 40 °C | DIN 51562 | mm ² /s | 50 |
| Viskosität bei 100 °C | DIN 51562 | mm ² /s | 9,5 |
| Flammpunkt | ISO 2592 | °C | 220 |
| Pourpoint | ISO 3016 | °C | -40 |
| TBN | ISO 3771 | mg KOH/g | 10 |

(Es handelt sich um Kennwerte, die im handelsüblichen Rahmen schwanken können.)

Januar 2004