

RUBIA 4400

15W-40



Multigrade oil for diesel engine

USES

- Specially developed for lubrication of turbocharged Euro 2 Diesel engines.
- Also suitable for all Diesel engines of previous generations, in severe service conditions.
- Suited for extended drain intervals (up to 30 000km according to manufacturers).
- Suited for off-road equipments' engines which need an API CH-4 lubricant.

PERFORMANCES

Specifications

ACEA E2
API CH-4/SJ

OEMS' approvals

MERCEDES BENZ 228.1
MAN 271
VOLVO VDS
MACK EO-L
MTU OL Type 1
CATERPILLAR TO-2
LIAZ 258-2 (B)
ALLISON C-4
KOMATSU

CUSTOMER BENEFITS

Technical performances

- Multigrade
- Very high viscosity index
- Excellent viscosity stability in operation
- Excellent detergency level
- Very high dispersancy level (avoids combustion soots agglomeration).
- Excellent antiwear and anticorrosion properties

CHARACTERISTICS

Rubia 4400	Units	SAE grade 15W-40
Volumetric mass at 15°C	kg/m ³	888
Viscosity at 100°C	mm ² /s	14,5
Viscosity index	-	142
Flash Point	°C	226
Pour point	°C	-30

The typical characteristics mentioned represent mean values.

TOTAL LUBRIFIANTS
16, rue de la République
92800 PUTEAUX
1/1

RUBIA 4400 15W-40
January 2004



This lubricant, when used according to our recommendations and for the purpose for which it is intended, presents no particular hazards.
A safety data sheet complying with current EC legislation can be obtained from your local commercial adviser.