



# MOLDOL LW 7085



## Concrete Demoulding Oil

### ANWENDUNGEN

#### Concrete demoulding oil- Gas concrete demoulding

- **MOLDOL LW 7085** is a special release agent for the manufacturing of gas concrete parts using steel form linings.
- Preferably to be used in neat form. Application by spray or brushes and rollers to obtain a thin surface film. It can be used preheated (up to 70°C) in order to optimize the application and to reduce significantly the consumption.
- Can be used in applications with deferred demoulding.

### EIGENSCHAFTEN

- **MOLDOL LW 7085** guarantees an excellent demoulding.
- leaves clean mould surfaces and a high surface quality of the concrete parts.
- the light colour of the product avoids darkening and staining of the surface.
- prevents corrosion on the mould surface and shows an excellent surface wettability.

CHARACTERISTICS	METHOD	UNIT	MOLDOL LW 7085
Density at 20°C	ISO 3675	kg/m <sup>3</sup>	881
Viscosity at 20 °C	ISO 3104	mm <sup>2</sup> /s	454
Viscosity at 40 °C	ISO 3104	mm <sup>2</sup> /s	130
Flash point	ISO 2719	°C	230
Pour point	ISO 3016	°C	-27

The nominal values given herein are subject of change without notification. Typical properties may vary slightly.

April 2005